

PROTECTION. PERFORMANCE. SCHAEFFER'S DEPENDABILITY.



HEAVY-DUTY DIESEL ENGINE OIL

- 700 SynShield™ Durability Advantage 15W-40**
Stronger durability and wear protection for equipment working long hours in harsh conditions. Meets and exceeds API CK-4. Backward compatible.
-
- 711 SynShield™ OTR Plus 10W-30**
Better fuel economy benefits while maintaining durability protection to keep engines running longer. Meets and exceeds API CK-4. Backward compatible.
-
- 722 SynShield™ Ultra Performance 10W-30**
Reduces wear and tear experienced in stop-and-go, short haul driving situations. Meets and exceeds API CK-4. Backward compatible.
-
- 6000 SynShield™ Max MPG 10W-30**
Better fuel economy and efficiency in 2017 engines. Meets and exceeds API FA-4. Not backward compatible.



RACING & EXTREME PERFORMANCE OILS

- Supreme 7000™ Synthetic Plus**
Gasoline race engines including those with flat tappet cams and those that are turbocharged or supercharged.
- 705 20W-50
708 15W-40
709 10W-30
-
- Supreme 9000™ Full Synthetic**
9001 5W-50
-
- Micron Moly® Racing Oil**
High performance gasoline engines and racing engines burning alcohol-based fuels.
- 110 SAE 30, 40 & 50
191 20W-50
-
- 9006 Supreme 9000™ Full Synthetic 2-Cycle Racing Oil**
Carbureted, electronic fuel injected (EFI) and direct injection (DFI) 2-cycle air-cooled and power valve engines.
-
- 706 Supreme 7000™ Synthetic Plus 2-Cycle TC-W3**
Water-cooled 2-cycle engines that meet NMMA TC-W3.



PASSENGER CAR & LIGHT DUTY TRUCK OIL

- Supreme 7000™ Synthetic Plus**
API SN, Resource Conserving, ILSAC GF-5.
- 701 5W-30
703 10W-30
-
- Supreme 9000™ Full Synthetic**
API SN, Resource Conserving, ILSAC GF-5, dexos1™ compliant.
- 9003D 5W-30
9004 5W-20
9005 0W-20



EUROPEAN ENGINE OIL

- 8007 Advanced European Performance Full SAPS 5W-30**
For highly tuned, advanced, four cylinder European gasoline and light duty diesel engines (except those with diesel particulate filters). Recommended for: VW 502.00/505.00; Mercedes-Benz 229.3; BMW Longlife-01; and JASO MA-2.
-
- 8008 Advanced European Performance Mid SAPS 5W-30**
For highly tuned, advanced, four cylinder European gasoline and light duty diesel engines. Recommended for: VW 502.00/505.00; ACEA C3-12; and Mercedes-Benz 229.31 and 229.51. Suitable for: BMW LONGLIFE-04; and VW 504.00/507.00.
-
- 8012 Advanced European Performance Heavy-Duty Diesel Engine Oil 5W-30**
Ultra high performance, low ash diesel oil for modern low emission engines. Recommended for ACEA E6-12, E7-12 and E9-12; API CJ-4/SN; and Mercedes-Benz 228.31 and 228.51.



MOTORCYCLE LUBRICANTS

- 170 Extreme Performance Full Synthetic Oil, 75W-140**
Heavy-duty or high performance transmissions, aftermarket 5-speed and 6-speed separate motorcycle transmissions and final drives, including standard and limited-slip differentials and shaft drive transmissions requiring the use of a hypoid type gear oil.
-
- 240 Extreme Performance V-Twin Primary Lube**
For use in the primary chain case of all Harley-Davidson Big Twin Models and in wet and primary/transmission common sumps found in Harley-Davidson Sportster models with wet clutches sharing the same sump as the transmission gears.
-
- 707 Extreme V-Twin Synthetic Plus Racing Oil 20W-50**
V-Twin engines and most motorcycles with separate engine compartments.

**YOUR EQUIPMENT'S
PERFORMANCE
IS ALWAYS WHAT MATTERS MOST.**



MULTI-PURPOSE GREASE

- 197 Moly Pure Synthetic Grease NLGI #2**
Bentone base. Low tack, water resistant. Wide temperature range, multi-purpose grease for heavy-duty equipment.
-
- 221 Moly Ultra NLGI #1 & #2**
Aluminum complex. Low tack, waterproof, all-purpose, extreme pressure grease for hot and wet applications, electric motor bearings and automotive wheel bearings.
-
- 229 Ultra Red Supreme NLGI #1 & #2**
Aluminum complex. Extra tack, waterproof, synthetic blend, red color grease for use where a clean grease is needed.
-
- 238 Ultra Supreme NLGI #1, #2 & #3**
Aluminum complex. Extra tack, waterproof, heavy-duty grease that meets Caterpillar's 5% moly specification.
-
- 274 Moly EP Synthetic Plus Grease NLGI #00, #0, #1 & #2**
Aluminum complex. Low tack, waterproof grease with synthetic blend base oils that enable the use of one grease for year-round use.
-
- 248 Moly Syngard™ 2000 NLGI #1, #2 & #3**
Bentone base. Extra tack, water resistant, versatile grease ideal for hot, wet or heavily loaded applications, especially when temperatures are above 350°F.
-
- 260 Perma Moly NLGI #1, #2 & #3**
Bentone base. Extra tack, water resistant grease for industrial bearings and machinery operating under heavy load and high temperatures.



SPECIALTY GREASE

- 206 Hi-Temp Cotton Picker Grease NLGI #00 & #0**
Non-melt base, bentone base grease with excellent thermal stability so cotton pickers can operate quickly on cool mornings without causing excessive wear.
-
- 228 Super HV Red NLGI #2**
Aluminum complex. Extra tack, waterproof, red grease for use where a clean grease is needed. ISO 460 for extra protection on heavily loaded, slow moving bearings.
-
- 278 Polyurea Grease NLGI #2**
Extreme pressure, polyurea grease to provide the severe lubrication requirements of plain and rolling-element bearings in long service applications and electric motor bearings.
-
- 286C Hi-Temp Grease With Copper NLGI #1.5**
Grease must reach 600°F or higher consistently before it will lubricate effectively. Silica gel thickener.

H-1 GREASES LISTED WITH OUR FOOD GRADE PRODUCTS.



FUEL ADDITIVES

- 131 Neutra™ Fuel Additive**
Gas, pre-2007 diesel and LPG fuels. Neutralizes fuel deposits, cleans fuel system components and lubricates upper cylinders. Contains more than 15PPM sulfur.
-
- 131C SoyUltra® Gasoline Additive**
Ashless fuel additive for gasoline and ethanol blends used in new and old 2-stroke and 4-stroke gasoline powered vehicles.
-
- Diesel Treat 2000™ Ultra Low Sulfur**
Meets DW-10 detergency specifications, upgrades #2 to premium diesel and increases lubricity. Contains less than 15PPM sulfur.
- 137 Summer, all season protection
137ULSW Winter protection (anti-gel and de-icer)
- (Ask about additional summer and winter additive blends.)
-
- CarbonTreat™ Premium**
Cleans and prevents deposits from forming in high-pressure fuel injection systems. Exceeds three times the DW-10 detergency specifications. Contains less than 15PPM sulfur.
- 137CTPS Summer (also available with extra cetane)
137CTPW Winter (also available with extra cetane)
137CTPA All season
-
- 139A SoyShield® All Season**
Made from soybean oil, meets DW-10 detergency specifications and upgrades #2 to premium. Contains less than 15PPM sulfur.
-
- 141 BioTreat™ Premium Diesel**
Upgrades B2-B50 blends to premium diesel, controls moisture and meets DW-10 detergency specifications. Contains less than 15PPM sulfur.
-
- 284 Diesel Hot Line**
Emergency treatment that immediately dissolves ice and wax in gelled diesel fuel. Contains less than 15PPM sulfur.
-
- 285 Fuel Shock**
Biocide to kill existing bacteria in diesel fuel; EPA registered.
-
- 300ULSW Arctic Shield™ + Ultra Low Sulfur**
Strong winter protection for over-the-road trucks dealing with high moisture content fuel. Less than 15PPM sulfur.
-
- 301 Tank Dry**
Moisture inhibiting fuel additive for gasoline, diesel and ethanol fuel tanks; meets EPA diesel fuel blending requirements. Contains less than 15PPM sulfur.

PDF



schaefferoil.com/technical

Download our technical data sheets and safety data sheets for the current product specifications and applications.



GEAR LUBES

167 Moly Full Synthetic Gear Lube 75W-140
ISO 150, 220, 320, 460, 680 & 1000
Full synthetic lube for use in all types of automotive and enclosed gear drives including worm gear drives.

209 Moly Universal Gear Lube
SAE 80, 90, 140 & 250
ISO 150, 220, 320, 460, 680 & 1000
Resists oxidation and thermal stress at temperatures 100°F to 150°F higher than conventional gear lubricants. Available with soluble moly #209A.

214S Supreme One For All 80W-140
Para-synthetic, multi-grade lubricant for use under severe wide ambient temperature ranges.

228PGL Super HV Pivot Gear Lube
Extreme pressure, thixotropic semi-fluid grease for use in gearboxes of center pivot irrigation systems. Aluminum complex.

239S Super Lube Supreme SAE 50
Para-synthetic, Cat TO-4 fluid for final drives in front end loaders and haul trucks and dozers, and Eaton® (Fuller) Roadranger and Meritor (Rockwell) transmissions not under extended warranty.

239S020 Super Lube Supreme Arctic with DYNAVIS® 0W-20
Full synthetic, multi-grade fluid for transmissions, torque convertors, final drives, hydraulics and wet brakes as well as machines with combined systems in Caterpillar and other OEM off-road equipment. Meets Caterpillar TO-4M. Viscosity index of >180.

Supreme Gear Lube 80W-90
ISO 150 & 220
Para-synthetic, extreme pressure lubricant for use in enclosed industrial and automotive gear drives.

267 With colloidal moly
293 With soluble moly
293A With soluble moly, non-tacky

268 Supreme Gear Lube SAE 140
ISO 320, 460 & 680
Para-synthetic, extreme pressure lubricant with soluble moly for use in enclosed industrial and automotive gear drives.

2937590 Supreme Gear Lube 75W-90
Para-synthetic lubricant with soluble moly and no tackifier; for use in equipment under severe wide ambient temperature ranges.

Supreme Gear Lube
ISO 320, 460 & 680
Para-synthetic, extreme pressure lubricant for use in enclosed industrial and automotive gear drives.

294 With soluble moly
294A With soluble moly, non-tacky

740 Synthetic Lube EP 80W-140
Full synthetic lubricant for use in all automotive gear drives, and Eaton® (Fuller) Roadranger and Meritor (Rockwell) under extended warranty.



GEAR LUBES

Synthetic Lube EP 75W-90
Full synthetic lubricant that improves fuel economy in heavy, mid and light duty automotive applications.

741 For use in Eaton® (Fuller) Roadranger and Meritor (Rockwell) under extended warranty.
751M With soluble moly. For use in applications not under extended warranty.

742 Synthetic Lube SAE 50
Full synthetic, non-extreme pressure lubricant designed for extended drain and severe service in heavy-duty manual transmissions.



TRANSMISSION & TORQUE CONVERTER FLUIDS

204SAT All-Trans Supreme® Full synthetic, multi-vehicle, automatic transmission fluid for use in GM Dexron® III(H); Ford MERCON® and MERCON® V; and Chrysler ATF +3 and +4.

205A Dexron®/MERCON® LV Automatic Transmission Fluid
Full synthetic, low viscosity, multi-vehicle fluid for GM Dexron® VI; Ford MERCON® LV; and JASO-1A (JWS 3309).

315 Simplex Supreme
Para-synthetic base for higher heat resistance and better cold weather performance. Universal transmission hydraulic fluid. Exceeds most farm tractor specs; check technical data sheet for full details.



INDUSTRIAL OILS

161 Moly Air Line Oil (with VarniShield®)
ISO 22, 32 & 46
Anti-wear oil for low pressure and high-pressure airlines and all types of pneumatic air tool systems where excessive operating temperatures are seen and protection against varnish is needed.

Moly EP Industrial Machine Lube
ISO 32, 46, 68, 100, 150 & 220
Heavy-duty, non-drip lubricant for slide and way systems that require a light to medium viscosity extreme pressure gear lube and other machine tools that require a general purpose extreme pressure oil.

203B Contains soluble moly for gears and bearings
203C Non-tacky for filtered systems

527 EcoShield™ Biodegradable Rock Drill Oil
ISO 46, 68, 100, 150, 220 & 320
Readily biodegradable, anti-wear, extreme pressure, emulsifiable oil for rock drills, hammers, drifters and pneumatically operated equipment. Meets USDA definition EO 13101 for bio-based products.



HYDRAULIC, TURBINE & COMPRESSOR FLUIDS

- 112 HTC Oil (with VarniShield®)**
ISO 22, 32, 46, 68, 100, 150 & 220
Anti-wear, rust and oxidation inhibited hydraulic lubricant with a high viscosity index. Helps reduce operating temperatures and varnish buildup in valves, and offers excellent thermal and oxidation stability.
-
- 113 VarniClean®**
Powerful cleaning action removes varnish buildup in hydraulic equipment. To protect from future buildup, use our hydraulic oils with VarniShield® after using VarniClean®.
-
- 158 Pure Synthetic Compressor Oil**
ISO 32, 46, 68, 100, 150 & 220
For use in oil flooded rotary vane and rotary screw compressors, screw type and reciprocating air compressors, pumps, vacuum pumps and blowers.
-
- 254 HTC Supreme (with VarniShield®)**
ISO 32, 46, 68, 100, 150 & 220
Para-synthetic for wider temperature range. Anti-wear, rust and oxidation inhibited hydraulic lubricant with a high viscosity index. Helps reduce operating temperatures and varnish buildup in valves, and offers excellent thermal and oxidation stability.
-
- 264 Pure Synthetic Hydraulic Oil**
ISO 32, 46, 68, 100, 150, 220, 320 & 460
Full synthetic, anti-wear, rust and oxidation inhibited hydraulic lubricant for hydraulic systems, steam and hydraulically driven turbine systems subjected to wide ambient temperature ranges. Extends oil drains and component service life.
-
- DI-LEX Supreme Hydraulic Fluid with DYNAVIS® (with VarniShield®)**
Para-synthetic dielectric oil for boom trucks, mobile equipment and hydraulic applications that operate in wide ambient temperature ranges.
275S ISO 32 & 46
275SW ISO 15 winter grade
-
- 288 HTC Extreme Performance Hydraulic Fluid With DYNAVIS® (with VarniShield®)**
ISO 15, 22, 32 & 46
Para-synthetic, multi-grade hydraulic fluid for year-round use in high pressure hydraulic systems of mobile equipment that require a fluid with the viscometric properties to operate over a wide range of ambient temperatures.
-
- 512 EcoShield™ Biodegradable HTC Oil**
ISO 32, 46 & 68
Biodegradable, environmentally friendly, ecologically responsive, non-toxic fluid for high pressure industrial, marine, construction and mobile hydraulic systems, turbines and circulating oil systems that are operated in environmentally sensitive areas. Meets USDA definition EO 13101 for bio-based products.



MACHINING OILS

- 125 Honing Oil**
Very low odor, chlorine-free, heavy-duty, active sulfur base, low viscosity oil for use on the honing and super-finishing of ferrous and certain non-ferrous metals as well as engine blocks and cylinders.
-
- 128N Odorless Sulfurized Cutting Oil**
Very low odor, chlorine-free, heavy-duty, active sulfur base cutting oil for use in moderate to severe machining operations of ferrous metals, alloys with low machinability ratings and certain non-ferrous metals.
-
- 160 Moly Slide And Way Lube (with VarniShield®)**
ISO 68, 100 & 220
Non-drip oil for machine tool slides and ways. Eliminates stick slip and chatter.
-
- 311 Synkool SS™**
Water-soluble, semi-synthetic, bio-stable, low foaming, non-staining metalworking fluid for use in grinding and other high speed light to heavy-duty machining operations.
-
- 324 Spindle Oil**
ISO 10 & 22
Low viscosity, anti-wear, high-speed spindle oil with soluble moly and VarniShield®.
-
- 411 Maxkool SS®**
Semi-synthetic, micro-emulsion metalworking fluid for a wide variety of alloys (not for use on very water reactive metals). For applications requiring moderate pressure fluid processes.
-
- 412 Tap Shield**
Water miscible, extreme pressure tapping fluid for use on all types of metals. Will not stain, excellent cooling, will not harden and leave residues. Low VOC content.
-
- 414 Maxkool Ultra**
Semi-synthetic, micro-emulsion metalworking fluid for high pressure circulating system. For use with ferrous and non-ferrous metals, aluminum, DEA free and biostable. (Not for use on very water reactive metals.)
-
- 511 Ultrakool SS®**
Semi-synthetic, micro-emulsion metalworking removal fluid with excellent foam control, bio-static resistivity and non-staining properties. For use in hard water, high pressure and low maintenance conditions. (Not for use on very water reactive metals.)
-
- 611 Machine Kleen™**
Made with surfactants and bio-static additives; penetrates bio-film and loosens debris, allowing quicker removal and better cleaning.



PERFORMANCE YOU CAN DEPEND ON.

Whatever the operating conditions, our products deliver the right protection your equipment needs today, tomorrow and in the years to come.



FOOD GRADE LUBRICANTS

Meet USDA 1998 H-1 guidelines; NSF registered.

190FG Penetro® Green H-1
Food grade chain lube and penetrating oil that cleans and protects against abrasive debris.

195 SuperTac Food Grade Grease H-1 NLGI #1 & #2
Our most waterproof food grade grease. Aluminum complex based with adhesive and cohesive additives.

269 Hydraulic Oil H-1
ISO 22, 32, 46, 68, 100, 150 & 220
Even in high temperatures, this full synthetic, low volatility lubricant reduces oil loss and emissions. Recommended for compressor applications.

Synthetic Food Grade Grease H-1 NLGI #2
Full synthetic, bentone-based grease ideal for high temperatures.

271 Tacky
272 Non-tacky (ISO 460 base oil, recommended for heavily loaded, slow moving bearings.)

276 Synthetic Food Grade Gear Lube H-1
SAE 90 & 140
ISO 100, 150, 220 & 460
Reduces operating temperatures; compatible with all types of seals and coatings.

280 Food Grade HTC
ISO 22, 32, 46, 68, 100, 150 & 220
Anti-wear oil for use in compressors, hydraulics, vacuum pumps and other general oiling applications.

287 Food Grade Flushing Agent
Light anti-wear food grade oil for use in flushing and cleaning gearboxes, hydraulic systems and compressors.

450 Food Grade H-1 High Temp Chain Lube
ISO 15, 150 & 220
Low volatility and high smoke point. Specialty grease used for chains exposed to temperatures up to 600°F.



OPEN GEAR, WIRE ROPE & THREAD LUBRICANTS

199 Silver Streak® Wire Rope Lubricant
Extends service life of all types of wire rope; forms a non-tacky film that resists dirt and abrasives and protects against rust.

200 Silver Streak® Multi-Lube Spray
Heavy-duty lubricant that remains soft and pliable over long period of time; forms an almost indestructible adhesive film.

200S Silver Streak® Special
Extreme pressure lubricant for open gears, dipper sticks, house rails and rollers. Available in various grades.

225 Moly Tool Joint
Anti-wear, extreme pressure lube for sealing pipe threads (except API thread pipes or pipe threads used in water applications).



SPECIALTY LUBRICANTS

132 Moly EP Oil Treatment
Extreme pressure protection for bearings, valve trains, pistons and piston rings. Increases oil pressure and reduces oil consumption.

116BC Bar & Chain Lube
Rapidly penetrates into pins and bushings on the chain; protects against wear and deposit buildups.

127 Moly Rock Drill Oil
ISO 32, 46, 68, 100, 150, 220 & 320
Anti-wear, extreme pressure, emulsifiable, low fog generating oil for use in pneumatically operated rock drills, drifters, jackhammers, sinkers and other air operated percussion tools and pneumatic equipment used in underground, surface mining, contractor and other industrial applications.

190 Penetro 90®
Lubricates all types of moving parts that have become difficult to operate. Triples protection against corrosion.

202 Moly Fifth Wheel Lube
Semi-synthetic, diluent-type, heavy duty, extreme pressure spray lubricant for easy application on fifth wheels.

213 Moly Liquid Chain Lube
ISO 150 = #1
ISO 460 = #2
Tacky, non-drip, extreme pressure oil for slow to moderate speed chains.

227 Moly Roller Chain Lube
Penetrating oil with moly for medium or high-speed chains. Will not collect dust. O-ring safe.

258 Clean & Cool
Coolant treatment additive for use with conventional-type antifreeze only. Prevents electrolysis, cavitation, scale and corrosion. Lubricates pumps and seals.

281 Heat Transfer Oil
Non-corrosive, non-fouling, paraffinic heat transfer fluid providing fast and efficient heat transfer when used in open loop or closed system applications with expansion tank temperatures up to 600°F. Also available as para-synthetic (281A) and full synthetic (281S).

Smokeless Hi-Temp Chain Lube
Full synthetic, smokeless lube with soluble moly for high temperature chains up to 450°F and spot temperatures to 600°F.

298 For smaller, fast moving chains.
298A For larger, slow moving chains.

319 Hi-Visc Boom Lube
High viscosity spray lubricant used for forklifts, aerial lifts, telescoping booms and other sliding metal surfaces found in industrial and construction applications.

743 SchaefferSeal™ Tire Sealant
Closes punctures and leaks with a permanent seal almost immediately. Prevents flats from punctures up to 3/16"; maintains tire pressure and reduces the risk of blowouts.



CLEANERS, DEGREASERS & RUST FIGHTERS

- 163 RustStop Outdoor**
Solvent cutback, non-staining, barium-free, water-displacing rust preventive solution that provides long term external protection to ferrous, galvanized and non-ferrous metal parts and equipment stored outdoors.
-
- 168 RustStop Indoor**
Solvent cutback, water displacing, barium-free, non-staining rust preventative solution that rapidly separates water displaced from metal surfaces after machining operations or alkali cleaning.
-
- 232 Vex Concentrate Cleaner**
Biodegradable, multi-purpose cleaner for industrial, field and household use. Highly concentrated, mix with water.
-
- 332 Turbo Red® Cleaner Concentrate**
Replaces the use of harsh caustics, cleans like a harsh caustic without the environmental and safety issues. Non-flammable, highly concentrated, mix with water.
-
- 333 Turbo Red® Universal Cleaner**
Less concentrated, broad dilution range. Effectively removes grease deposits, dirt, oils, road soils, soot and more.
-
- 266 Citrol®**
Biodegradable, heavy-duty, citrus-based degreaser with astonishing cleaning power. Check technical data sheet for VOC requirements. Ask about our concentrated strength Citrol® products.
-
- 266LV Citrol® Low VOC**
Biodegradable, heavy-duty, citrus-based degreaser with astonishing cleaning power and low VOC content.
-
- 350 Crete Crusher**
Effectively dissolves up to 1/4" of concrete residue; safe on most surfaces – spot test before using.
-
- 721 RustEnder**
Environmentally friendly rust and corrosion remover.
-
- 4002 Bed Release Agent**
Partially biodegradable asphalt release; rapid and easy separation of asphalt from beds of haul trucks. Check state requirements before using.
-
- 4009 Super Slick™**
Soy-based asphalt release; rapid and easy separation of asphalt from beds of haul trucks. Check state requirements before using.



SURFACTANTS & SPREADER-STICKERS

- 233 Wet-Sol® Concentrate**
For irrigated and non-irrigated crops and all types of turfs and landscapes. In CA: not for spreader-sticker use.
-
- 233G Wet-Sol® Gro**
Contains bio-stimulants, B-complex vitamins, fermentation products and hormones; not a plant food.
-
- 235 Wet-Sol® 99**
Highly concentrated; ideal for aerial applications and reduced spray volumes.
-
- 242 DynaHume™**
10% humic acid product. Forms aggregates in soil to increase water infiltration, reduces drought stress especially in poor soils by increasing the water holding capacity of the soil, reduces nitrogen salt injury and stabilizes nitrogen.
-
- 243 Rhizozyme™ Supreme**
Delivers beneficial microbes, improves soil structure and improves fertilizer uptake.
-
- 245 StomaBoost™ Supreme**
A concentrated NPK fertilizer nutrient solution containing micro-nutrients boron, manganese, zinc and copper.
-
- 246 Rhizozyme™ Plus**
Fortified with B vitamins, enzymes, other growth stimulators; encourages food to be more available to the plant and micro-organisms in the soil to promote the symbiotic relationship between the two.
-
- 247 StomaBoost™ Plus**
Contains B vitamins, enzymes and other growth stimulators. Optimizes the indigenous soil microbes.

Each state has its own label regulations; product availability may vary by state. Ask your Schaeffer rep for details.



GOOD PEOPLE. GREAT PRODUCTS.

Founded in 1839, Schaeffer's Specialized Lubricants is a sixth-generation, family-owned company that delivers the right solution to every lubrication challenge. Our lubricants provide strong equipment durability and fuel economy benefits, allowing you to maximize your equipment's performance and return on investment.



800-325-9962



schaefferoil.com

SL-1475B (02/17)